

In the claims:

For the Examiner's convenience, all pending claims are presented below with changes shown in accordance with the mandatory amendment format.

1. (Currently Amended) A method to train image classification, comprising:
measuring noise in a first image; and
generating a noise-reduced second image from the first image;
aggregating the difference between the first image and the second image into a noise
feature vector; and
training a classification model from the noise feature vector to classify a third ~~second~~
image as a natural image versus an artificial image from ~~[[the]]~~ noise in the third image.
2. (Canceled)
3. (Currently Amended) The method of claim 1 ~~[[2]]~~, wherein generating the
noise-reduced third image further comprises~~[[:]]~~ applying a median filter to the first image.
4. (Currently Amended) The method of claim 1 ~~[[2]]~~, wherein generating the
noise-reduced third image further comprises~~[[:]]~~ applying a Gaussian filter to the first image.
5. (Currently Amended) The method of claim 1 ~~[[2]]~~, wherein generating the
noise-reduced third image further comprises~~[[:]]~~ applying a Wiener filter to the first image.
6. (Original) The method of claim 1, wherein the first image further comprises a
frame in a video stream.

7. (Previously Presented) A method to train image classification, comprising:
generating a feature vector from an image; and

training a classification model to classify a second image as a slide image versus a comic image, from the feature vector, wherein the feature vector further comprises at least one feature of an image selected from the group consisting of at least one text block feature of the image, at least one edge-location feature of the image, and at least one aspect ratio of the image.

8. (Original) The method of claim 7, wherein generating a feature vector from an image further comprises:

generating an aggregated feature vector from an image.

9. (Canceled)

10. (Original) The method of claim 7, wherein the image further comprises a frame in a video stream.

11. (Previously Presented) A method to classify an image as a slide image versus a comic image, comprising:

receiving a feature vector of the image, wherein the feature vector is generated from at least one feature of an image selected from the group consisting of at least one text block feature of the image, at least one edge-location feature of the image, and at least one aspect ratio of the image;

classifying the image as slide image versus comic image, from the feature vector; and
generating the classification of the image.

12. (Original) The method of claim 11, wherein the classification is performed on a set of video frames of a video sequence, and the most likely classification result emerging out of the classification results of the individual frames is taken as the class of the video sequence.

13. (Canceled)

14. (Currently Amended) A method to classify ~~[[an]]~~ a first image as natural image versus artificial image, further comprising:

receiving a feature vector of the first image, wherein the feature vector comprises one or more of a noise vector and a sharpness vector;

classifying the first image as natural image versus artificial image~~[[,]]~~ from the feature vector; and

generating the classification of the image;

wherein the classifying is based on training from one or more of a noise feature vector and a sharpness feature vector, the noise feature vector comprising the aggregation of the difference between a second image and a noise-reduced third image generated from the second image, and the sharpness feature vector comprising the aggregation of the difference between the second image and a blurred fourth image generated from the second image.

15. (Original) The method of claim 14, wherein the classification is performed on a set of video frames of a video sequence, and the most likely classification result emerging out of the classification results of the individual frames is taken as the class of the video sequence.

16.-17. (Canceled)

18. (Currently Amended) An image classification system comprising:
a feature extraction component[[,]] to extract[[ing]] a feature that distinguishes a
frame in a video stream between a naturally-looking image versus an artificially-looking
image; and
a training system[[,]] operably coupled to the feature extraction component to train a
classification model to distinguish the feature based on one or more of a noise feature vector
and a sharpness feature vector, the noise feature vector comprising the aggregation of the
difference between a first image and a noise-reduced second image generated from the
second image, and the sharpness feature vector comprising the aggregation of the difference
between the first image and a blurred third image generated from the first image.

19. (Canceled)

20. (Original) The system of claim 18, wherein the classification is performed on
a set of video frames of a video sequence, and the most likely classification result emerging
out of the classification results of the individual frames is taken as the class of the video
sequence.

21. (Currently Amended) A system to classify an image comprising:

a processor;

a storage device coupled to the processor;

software means operative on the processor to:

train classification of at least one [[of]] image[[s]] as either a natural image or
an artificial image, ~~wherein the software means further comprises a generator of a~~
~~noise vector of each of the at least one images~~ based on a noise feature vector

including the aggregation of the difference between a first image and a noise-reduced second image generated from the first image; and
classify the at least one image as either a natural image or an artificial image based on the training.

22. (Original) The system of claim 21, wherein the at least one image further comprises at least one frame in a video stream.

23. (Canceled)

24. (Previously Presented) A system to classify an image, comprising:
a processor;
a storage device coupled to the processor;
software means operative on the processor to train classification of at least one image as either a slide image or an comic image, wherein the software means further comprises a generator of a feature vector from at least one feature of an image selected from the group consisting of at least one text block feature of the image, and at least one edge-location feature of the image, and at least one aspect ratio of the image.

25. (Original) The system of claim 24, wherein the at least one image further comprises at least one frame in a video stream.

26-29. (Canceled)

30. (Previously Presented) A system to classify an image, comprising:
a processor;
a storage device coupled to the processor; and

software means operative on the processor to classify an image as either a slide image or an comic image;

wherein the software means further comprises a generator of a feature vector from at least one feature of an image selected from the group consisting of at least one text_block feature of the image, at least one edge-location feature of the image, and at least one aspect ratio of the image.

31. (Original) The system of claim 30, wherein the image further comprises a frame in a video stream.

32. (Canceled)

33. (Currently Amended) A computer-readable medium having computer-executable instructions to cause a computer to perform a method comprising:

generating a feature vector from a first image, wherein the feature vector is one or more of a noise vector and an edge-sharpness vector; and

training a classification model to classify ~~a second~~ the first image as a natural image versus an artificial image, from the feature vector;

wherein ~~the feature vector is one or more of a noise vector and an edge-sharpness vector~~ classifying is based on training from one or more of a noise feature vector and a sharpness feature vector, the noise feature vector comprising the aggregation of the difference between a second image and a noise-reduced third image generated from the second image, and the sharpness feature vector comprising the aggregation of the difference between the second image and a blurred fourth image generated from the second image.

34. (Original) The computer-readable medium of claim 33, wherein the first image further comprises a frame in a video stream.

35-36. (Canceled)

37. (Previously Presented) A computer-readable medium having computer-executable instructions to cause a computer to perform a method comprising:

generating a feature vector from a first image; and

training a classification model to classify a second image as a slide image versus a comic image, from the feature vector, wherein the feature vector is generated from at least one feature of an image selected from the group consisting of at least one text block feature of the image, at least one edge-location feature of the image, and at least one aspect ratio of the image.

38. (Original) The computer-readable medium of claim 37, wherein the first image further comprises a frame in a video stream.

39. (Canceled)

40. (Previously Presented) A computer-readable medium having computer-executable instructions to cause a computer to perform a method comprising:

receiving a feature vector of the image, wherein the feature vector is generated from at least one feature of an image selected from the group consisting of at least one text block feature of the image, at least one edge-location feature of the image, and at least one aspect ratio of the image;

classifying the image as slide image versus comic image, from the feature vector; and

generating the classification of the image.

41. (Original) The computer-readable medium of claim 40, wherein the classification is performed on a set of video frames of a video sequence, and the most likely classification result emerging out of the classification results of the individual frames is taken as the class of the video sequence.

42. (Canceled)

43. (Currently Amended) A computer-readable medium having computer-executable instructions to cause a computer to perform a method comprising:

receiving a feature vector of ~~[[the]]~~ a first image, wherein the feature vector is one or more of a noise vector and an edge-sharpness vector;

classifying the first image as natural image versus an artificial image~~[[,]]~~ from the feature vector; and

generating the classification of the image;

wherein the classifying is based on training from one or more of a noise feature vector and a sharpness feature vector, the noise feature vector comprising the aggregation of the difference between a second image and a noise-reduced third image generated from the second image, and the sharpness feature vector comprising the aggregation of the difference between the second image and a blurred fourth image generated from the second image.

44. (Previously Presented) The computer-readable medium of claim 43, wherein the classification is performed on a set of video frames of a video sequence, and the most

likely classification result emerging out of the classification results of the individual frames is taken as the class of the video sequence.

45. (Currently Amended) An apparatus to classify at least one image, comprising:
a processor;
a storage device coupled to the processor; and
a software component operative on the processor to train classification of at least one image as either a natural image or an artificial image, wherein the software component further comprises a generator of a noise vector of each of the at least one image;
wherein the classification is based on training from one or more of a noise feature vector comprises an aggregation of the difference between a first image and a noise-reduced second image generated from the first image.

46. (Previously Presented) The apparatus of claim 45, wherein the at least one image further comprises at least one frame in a video stream.

47. (Canceled)

48. (Previously Presented) An apparatus to classify at least one image, comprising:
a processor;
a storage device coupled to the processor;
a software component operative on the processor to train classification of at least one image as either a slide image or an comic image, wherein the software component further comprising a generator of a feature vector from at least one feature of an image selected from

the group consisting of at least one text block feature of the image, at least one edge-location feature of the image, and at least one aspect ratio of the image.

49. (Previously Presented) The apparatus of claim 48, wherein the at least one image further comprises at least one frame in a video stream.

50. (Canceled)

51. (Currently Amended) An apparatus to classify an image, comprising:
a processor;
a storage device coupled to the processor; and
a software component operative on the processor to classify ~~[[an]]~~ a first image as either a natural image or an artificial image, wherein the software component further comprises a feature vector generator to generate ~~[[of]]~~ one or more of a noise vector ~~of the image~~ and a edge-sharpness vector of the first image;

wherein the classifying is based on training from one or more of a noise feature vector and a sharpness feature vector, the noise feature vector comprising the aggregation of the difference between a second image and a noise-reduced third image generated from the second image, and the sharpness feature vector comprising the aggregation of the difference between the second image and a blurred fourth image generated from the second image.

52. (Original) The apparatus of claim 51, wherein the classifying is performed on a set of video frames of a video sequence, and the most likely classification result emerging out the classification results of the individual frames is taken as the class of the video sequence.

53.-54. (Canceled)

55. (Previously Presented) An apparatus to classify an image, comprising:

a processor;

a storage device coupled to the processor; and

a software component operative on the processor to classify an image as either a slide image or an comic image, wherein the software component further comprising a generator of a feature vector from at least one feature of an image selected from the group consisting of at least one text block feature of the image, at least one edge-location feature of the image, and at least one aspect ratio of the image.

56. (Original) The apparatus of claim 55, wherein the classifying is performed on a set of video frames of a video sequence, and the most likely classification result emerging out the classification results of the individual frames is taken as the class of the video sequence.

57. (Canceled)

58. (Currently Amended) A method to train image classification, comprising:

measuring sharpness in a first image; and

generating a blurred second image from the first image;

aggregating the difference between the first image and the second image into a sharpness feature vector; and

training a classification model from the sharpness feature vector[[,]] to classify a ~~second~~ third image as a natural image versus an artificial image[[,]] from sharpness in the third image.

59. (Canceled)

60. (Previously Presented) The method of claim 59, wherein generating a blurred third image from a first image further comprises:

applying a Gaussian filter to the first image.

61. (Original) The method of claim 58, wherein the first image further comprises a frame in a video stream.

62. (Original) The method of claim 58, wherein the first image further comprises all frames in a video stream.